



Material Safety Data Sheet

FMC-200 and FMC-201

MSDS No. 515

Date of Preparation: October 20, 2010

Revision: 0012

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: FMC-200 and FMC-201

General Use: Polyurethane Elastomer

Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042

Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel

Domestic 800-255-3924

International 813-248-0585

Section 2- Hazards Identification

Hazard Designation:

Europe



Canada



HMIS	
H	1
F	1
R	1


N: Dangerous for the environment

Risk Phrases pertaining to particular dangers

R52/53: Harmful to aquatic organisms; may cause long term adverse effects in the aquatic environment.

Classified according to Articles 6 & 7 of Directive 1999/45/EC

Section 3 - Composition / Information on Ingredients

Component	ACGIH TWA	OSHA PEL	Hazard Designation	Weight Percent (%)
Polysulphide Polymer CAS Number: 68611-50-7	None Esatblished	None Esatblished	 N	50-55

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water; remove contaminated clothing and launder before reuse; seek medical attention if rash develops.

Ingestion: Do not induce vomiting unless instructed by a physician. Contact physician immediately

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flash Point: >300 °F (150°C)

Flash Point Method: COC

LEL: Not Established **UEL:** Not Established


Flammability Classification: Non-Flammable

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Hazardous Combustion Products: oxides of carbon, oxides of sulfur, hydrocarbons, hydrogen sulfide.

Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.



Section 6 - Accidental Release Measures

Spill /Leak Procedures: Only properly protected personnel should remain in the spill area; dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely.

Section 7 - Handling and Storage

Handling Precautions: Minimize breathing of vapors and avoid prolonged or repeated contact with skin. Wear proper protective equipment. If ventilation is not sufficient, wear proper respiratory equipment. Avoid moisture contamination. Reseal partial containers. Use good general housekeeping procedures.

Storage Requirements: Store in cool dry, well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Follow OSHA respirator regulations 29 CFR 1910.134 and European Standard EN 149; wear an MSHA/NIOSH or European Standard EN149 approved respirator. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas

Protective Clothing/Equipment: Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.



Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Physical State

Appearance and Odor: Black viscous liquid,
Mercaptan odor

Vapor Pressure: Not Determined

Vapor Density (Air=1): Not Determined

Specific Gravity (H₂O=1, at 4 °C): 1.30

pH: Not Determined

Water Solubility: Insoluble

Boiling Point: >350 °F (177 °C)

Freezing/Melting Point: N/A

Viscosity: <140 poise

% Volatile: None

Evaporation Rate: None

Section 10 - Stability and Reactivity

Stability: These products are stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Strong acids and strong oxidizers

Hazardous Decomposition Products: Thermal oxidative decomposition can produce oxides of carbon, oxides of sulfur, hydrocarbons and hydrogen sulfide.

Section 11- Toxicological Information

	LD50 Oral	LD50 Dermal
Polysulphide Polymer	Rat: >5000 mg/kg	Rat: >7800 mg/kg

Section 12 - Ecological Information

For Polysulphide Polymer:

Ecotoxicity in water: 1000 mg/l (Fish)

This product is not easily biodegradable.

Section 13 - Disposal Considerations

Disposal: Must be disposed of in accordance with local regulations.

Section 14 - Transport Information

DOT

Not Regulated

IATA

Not Regulated

IMDG

Not Regulated

Section 15 - Regulatory Information

TSCA Inventory Status (40 CFR710): All components of these formulations are listed in the TSCA Inventory.

California Proposition 65: These products do not contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

Canadian Regulations;


WHMIS Identification: **D2A, D2B**

CDSL/NDL (Canadian Domestic Substance List/Non Domestic Substance List): **Listed on CDSL**



Section 15 - Regulatory Information (continued)

Labeling according to EEC Directive

Risk Phrases	Symbol(s) Required for EU Label	Safety Phrases
<p>R50/53: Very toxic to aquatic organisms may cause long term adverse effects in the aquatic environment.</p> <p>R61: May cause harm to the unborn child.</p> <p>R62: Possible risk of impaired fertility.</p>	 <p>N: Dangerous for the environment</p>	<p>S61: Avoid release to the environment. (See MSDS).</p>

16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 1907/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives.