

SDS No. 7130

Section 1 - Identification

1.1 Product Identifier: Ease Release 207, 307, 407, and 82-36

1.2 General Use: Mold Release Agent

1.3 Manufacturer: Mann Release Technologies, Inc.,

5600 Lower Macungie Rd., Macungie, PA 18062 Phone (610) 252-5800, FAX (610) 252-6200

1.4 Emergency Contact: Chem-Tel Domestic: 800-255-3924 International: 813-248-0585

Section 2 - Hazard(s) Identification

2.1 Classification of the substance or mixture:

H226 Flammable liquid – Category 3 **H304** Aspiration Hazard – Category 1

2.2 GHS Label elements, including precautionary statements

Pictogram(s):



Signal word: Danger

H226 Flammable liquid and vapor

Physical Hazard

H304 May be fatal if swallowed and enters airways.

General Precautions:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

Prevention Precautions

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response Precautions

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water or shower.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P370 + P378 In case of fire: Use Water Fog, Dry Chemical, and Carbon Dioxide Foam to

extinguish.

P391 Collect spillage.



SDS No. 7130

Storage Precautions

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal Precautions

P501 Dispose of contents/container according to local, state and federal laws.

Hazards not otherwise classified (HNOC) or not covered by GHS – none known

Section 3 - Composition / Information on Ingredients

3.1 Substances

The following ingredients are hazardous according to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR 1910.1200:

CAS-No.	Chemical Name	Concentration (% w/w)
64742-48-9	Naphtha (Petroleum), hydrotreated heavy	80% - 95%

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately. **Eye Contact:** Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water.

Ingestion: Do not induce vomiting unless instructed by a physician. Never give anything by mouth to an unconscious person.

- 4.2 Most important symptoms and effects, both acute and delayed None known.
- 4.3 After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

- **5.1 Extinguishing Media:** Water Fog, Dry Chemical, and Carbon Dioxide Foam
- 5.2 Special hazards arising from the substance or mixture: None known.
- 5.3 Advice for firefighters: Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam. Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure demand or positive-pressure mode.

Section 6 - Accidental Release Measures

- **6.1** Personal precautions, protective equipment and emergency procedures: Only properly protected personnel should remain in the spill area; dike and contain spill. Stop or reduce discharge if it can be done safely.
- **6.2 Environmental precautions:** Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas. **Additional information:**



SDS No. 7130

Land Spill: Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Prevent entry into waterways, sewer, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Use clean non-sparking tools to collect absorbed material. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Large Spills: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Water Spill: Stop leak if you can do it without risk. Eliminate sources of ignition. Warn other shipping. If the Flash Point exceeds the Ambient Temperature by 10 °C or more, use containment booms and remove from the surface by skimming or with suitable absorbents when conditions permit. If the Flash Point does not exceed the Ambient Air Temperature by at least 10 °C, use booms as a barrier to protect shorelines and allow material to evaporate. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

- 6.3 Methods and material for containment and cleaning up: Put on appropriate protective gear including NIOSH/MSHA approved self-contained breathing apparatus, rubber boots and heavy rubber gloves. Dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely. Follow applicable OSHA regulations (29 CFR 1910.120) for disposal.
- **Reference to other sections:** See Section 3 for list of Hazardous Ingredients; Sections 8 for Exposure Controls; and Section 13 for Disposal.

Section 7 - Handling and Storage

- **7.1 Precautions for safe handling:** Use good general housekeeping procedures. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices.
- 7.2 Conditions for safe storage, including any incompatibilities: Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated place away from heat, direct sunlight, strong oxidizers and any incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Avoid water contamination.
- **7.3 Specific end use(s):** These precautions are for room temperature handling. Other uses including elevated temperatures or aerosol/spray applications may require added precautions.

Section 8 - Exposure Controls / Personal Protection

8.1 Control parameters:

Component	CAS-No.	Value	Control Parameters	Basis
Naphtha (Petroleum), hydrotreated heavy	64742-48-9	TWA	400 mg/m3	OSHA Z - 1



SDS No. 7130

8.2 Exposure controls:

Respiratory Protection: Respiratory protection is not normally required when using this product with adequate local exhaust ventilation. Where risk assessment shows air-purifying respirators are appropriate, follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators equipped with appropriate filter cartridges as a backup to engineering controls.

Hand Protection: Wear any liquid-tight gloves such as butyl rubber, neoprene or PVC.

Eye Protection: Safety glasses with side shields per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Other Protective Clothing/Equipment: Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. Wash thoroughly after handling.

Section 9 - Physical and Chemical Properties

9.1 Information on basic physical and chemical properties:

Appearance : Liquid Odor/Threshold: Faint pH: N.A. (non-aqueous)

Melting Point/Freezing Point: N.A. Low/High Boiling Point: 331°F- 349°F

Flash Point: 113 °F Evaporation Rate: 0.1 Flammability: N/A

UEL/LEL: LEL: 0.7 UEL: 6.0

Vapor Pressure: 0.1 kPa (0.75 mm Hg) at 20 °C

Vapor Density (Air=1): 5 at 101 kPa Specific Gravity (H₂O=1, at 4 °C):

Water Solubility: Insoluble Partition coefficient: Negligible Auto-ignition temperature: 653°F

Decomposition temperature: Not available

Viscosity: 1.2 cSt (1.2 mm2/sec) at 40 °C | 1.6 cSt

(1.0 mm2lsec) at 20°C **% Volatile:** Nil

Section 10 - Stability and Reactivity

- **10.1 Reactivity:** No hazardous reactions if stored and handled as prescribed/indicated., No corrosive effect on metal. Not fire propagating.
- **10.2** Chemical stability: These products are stable at room temperature in closed containers under normal storage and handling conditions.
- **10.3 Possibility of hazardous reactions:** Hazardous polymerization cannot occur.
- 10.4 Conditions to avoid: none known
- 10.5 Incompatible materials: strong bases and acids
- **10.6 Hazardous decomposition products:** Thermal oxidative decomposition can produce carbon oxides, gasses/vapors, and traces of incompletely burned carbon compounds.

Section 11- Toxicological Information

11.1 Information on toxicological effects:

Skin Corrosion/Irritation: Mildly irritating to skin with prolonged exposure. Based on test

data for structurally similar materials.

Acute Toxicity (Rabbit): LD50 > 5000 mg/kg

Serious Eye Damage/Irritation: May cause mild, short-lasting discomfort to eyes. Based on test

data for structurally similar materials.



SDS No. 7130

Respiratory/Skin Sensitization: Not expected to b6 a respiratory sensitizer and Not expected to be a germ cell mutagen. Based on test data for structurally similar materials.

Germ Cell Mutagenicity: Not expected to be a germ cell mutagen. Based on test data for structurally similar materials.

Carcinogenicity: No component of these products present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC, ACGIH or NTP.

Reproductive Toxicity: Not expected to b€ a reproductive toxicant. Based on test data for structurally similar materials.

Specific Target Organ Toxicity – Single Exposure: Not expected to cause organ damage from a single exposure

Specific Target Organ Toxicity – Repeated Exposure: Not expected to cause organ damage from prolonged or repeated exposure. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECO Guide line 408 413 422

Aspiration Hazard: May be fatal if swallowed and enters airways. Based on physicochemical properties of the material

Acute Toxicity: (Rat) 8 hours LC50 > 5000mg/m3 (Vapor). Minimally Toxic. Based on test data for structurally similar materials.

Chronic Exposure: no data

Potential Health Effects - Miscellaneous: no data

Vapor/aerosol concentrations above recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects.

Prolonged and/or repeated skin contact with low viscosity materials may defat the skin resulting in possible irritation and dermatitis. Small amounts of Liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Section 12 - Ecological Information

- **12.1 Toxicity:** Material May cause long{erm adverse effects in the aquatic environment.
- 12.2 Persistence and Degradability: no data
- 12.3 Bioaccumulative Potential: no data
- **12.4 Mobility in Soil:** Material is highly volatile, will partition to air. Will not partition to sediment and wastewater solids.
- 12.5 Results of PBT and vPvB assessment: no data
- 12.6 Other Adverse Effects: no data

Section 13 - Disposal Considerations

13.1 Waste treatment methods: Under Resource Conservation and Recovery Act (RCRA) it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste as defined in 40 CFR Part 261. Waste management should be in full compliance with federal, state and local laws. Empty containers retain product residue which may exhibit hazards of material, therefore to not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Section 14 - Transport Information



SDS No. 7130

14.1 UN number: 1866

14.2 UN proper shipping name: Resin solution

14.3 Transport hazard class(es): 3

14.4 Packing group: III

14.5 Environmental hazards: none known14.6 Special precautions for user: none known

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: not

applicable

Section 15 - Regulatory Information

15.1 Safety health and environmental regulations/legislation specific for the substance or mixture:

REACH: Regulation (EC) No 1907/2006 of The European Parliament and of The Council of December 2006 (including amendments and corrigenda as of 17 February 2016): This product complies with REACH or is not subject to regulation under REACH. The product does not contain an ingredient listed on either the Candidate List or Authorization List for Substances of Very High Concern (SVHC).

In the United States (EPA Regulations):

TSCA Inventory Status (40 CFR710): All components of this formulation are listed in the TSCA Inventory. No component of this formulation has been determined to be subject to manufacturing or use restrictions under the Significant New Use Rules (SNURs).

SARA 302 Components: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 313.

SARA 311/312 Hazards: Fire. Immediate health

State Right-to-Know

ComponentCAS#StateNaphtha (Petroleum),6429-90-5MN, NJ, PA


hydrotreated heavy

<u>California Proposition 65</u>: This product does not intentionally contain any chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.

15.2 Chemical safety assessment: No chemical safety assessment has been carried out for this substance/mixture by the supplier.

16 - Other Information

HMIS			
Н	2		
F	3		
R	0		





SDS No. 7130

Revision: 3

Date Prepared: November 3, 2023

Glossary: ACGIH-American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS-Chemical Abstract Service; Chemtrec-Chemical Transportation Emergency Center (US); CHIP-Chemical Hazard Information and Packaging; DSL-Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; GHS-Globally Harmonized System of Classification and Labelling of Chemicals; HMIS-Hazardous Material Information Service; IATA-International Air Transport Association; IMDG-International Maritime Dangerous Goods Code; LC-Lethal Concentration; LD-Lethal Dose; LEL-Lower Explosion Level; NFPA-National Fire Protection Association; OEL-Occupational Exposure Limit; OSHA-Occupational Safety and Health Administration, US Dept. of Labor; PEL-Permissible Exposure Limit; SARA (Title III)-Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act,

Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality; TLV-Threshold Limit Value; TSCA-Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; UEL-Upper Explosion Level; US DOT-US Department of Transportation; WHMIS-Workplace Hazardous Materials Information System.

Disclaimer: The information contained in this Safety Data Sheet (SDS) is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This SDS is prepared to comply with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) as prescribed by the United States (US) Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 (REACH).

Classifications of the chemical in accordance with 29 CFR 1910.1200, signal word, hazard and precautionary statement(s), symbol(s) and other information are based on listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS and EC No 1907/2006 and are considered trade secrets under US Federal Law (29 CFR and 40 CFR), Canadian Law (Health Canada Legislation), and European Union Directives.