307 UTE

SCULPTURING EPOXY

25% LIGHTER FORMULA
 NO SOLVENTS

- NO SOLVENTS
 NON-TOXIC
- NUN-IUXIC
- SANDABLE
- PAINTABLE
- PIGMENTABLE

*ENVIRONMENTALLY SAFE *CLEANS UP WITH WATER *IDEAL FOR UNDERWATER APPLICATIONS

307 LITE is a 100% solids light-weight epoxy system specially formulated to a trowelable paste consistency for sculpturing and fabricating projects. **307 LITE** will cure into an extremely strong and light-weight plastic that is easily sanded or shaped. **307 LITE** can be tinted or painted and will even accept stains. **307 LITE** bonds well to most surfaces including fiberglass, foams, metal, wood and concrete. **307 LITE** is solvent free so it won't melt or dissolve foam surfaces.

307 LITE can be used as a sculpturing or texturing veneer over other surfaces and is thick enough for immediate embossing upon placement. **307 LITE** is ideal for indoor or outdoor exhibit projects where strength and durability are desired. **307 LITE** can also be used as a patching compound to repair broken or damaged exhibits. **307 LITE** is the recommended formula for underwater applications.

PROPERTIES OF 307 LITE

Compressive Strength ASTM D-695 Tensile Strength ASTM D-638 Viscosity Mix Ratio Pot Life Cure Time Weight per Gallon Packaging 11,500 psi (min) 2,100 psi (min) Thick paste 1:1 60 minutes @70°F 10-14 hours 8.25 lbs. 2, 10, and 100 Gallon Kits

MIXING INSTRUCTIONS

Thoroughly mix equal amounts of Part A and Part B by volume until streak free. Wearing protective gloves, trowel or spread the **307 LITE** and immediately texture, emboss or finish as desired. Small amounts of water may be used to help prevent the **307 LITE** from sticking to the gloves. Do not apply **307 LITE** when ambient temperatures or surface temperatures are below **50 E**

POLYGEM, Inc. P.O. Box 609 West Chicago, IL 60186 www.polygem.com Ph: (630) 231-5600 Fx: (630) 231-5604