



Armorstone

Brushable Gel Coat

- NO SOLVENTS
- NON-TOXIC
- PAINTABLE
- WATERPROOF

***ENVIRONMENTALLY SAFE**

***IDEAL FOR EPS FOAM**

ARMORSTONE is a 100% solids epoxy that is ideal for the gel coating of most surfaces including EPS and other foams. **ARMORSTONE** will cure into a n extremely strong durable "hard-shell" plastic that can be sanded and painted. Armorstone is solvent free so it won't melt, distort or dissolve foam surfaces.


ARMORSTONE is specially formulated to a creamy smooth consistency that can be applied by brush, roller and even sprayed. **ARMORSTONE** can also be used as a high-strength bonding or laminating adhesive.

PROPERTIES OF ARMORSTONE

Tensile Strength	8,420 psi (min)
Shore D Hardness	80-75
Shrinkage	1% Max
Viscosity	Heavy Weight Motor Oil
Mix ratio	1:1
Pot Life	45 Minutes @ 70F
Cure Time	16-24 Hours
Color Mixed	Light Grey
Packaging	2 Gal, 10 Gal & 100 Gal Kit

MIXING INSTRUCTIONS

Thoroughly blend equal amounts of the part A and Part B by volume until streak free and uniform in color.



POLYGEM, Inc.
P.O. Box 609
West Chicago, IL 60186

www.polygem.com
Ph: (630) 231-5600
Fx: (630) 231-5604