



CAMMO FLEX

- NO SOLVENTS
- NON-TOXIC
- PAINTABLE
- PIGMENTABLE

ENVIRONMENTALLY SAFE

CAMMO FLEX is a 100% solids epoxy system specially formulated to provide a flexible surface for sculpturing and modeling projects. **CAMMO FLEX** will cure into a durable rubber that will accommodate movement and even bend upon cure.

CAMMO FLEX is available in an untinted liquid or gel formulas and can be pigmented or painted. **CAMMO FLEX** is ideal for vines, trees, and leaves or other projects that require a more "lifelike" texture or feel. **CAMMO FLEX** is furnished in convenient pre-measured kits for easy and accurate mixing of the product.

PROPERTIES OF CAMMO FLEX

Compressive / Elongation	50+%
Tensile Strength ASTM D-638	1,000 p.s.i.
Hardness Shore A	90/85
Hardness Shore D	50/45
Viscosity	Pourable or Gel
Mix Ratio	2:1 by Volume
Pot Life	60 minutes @70°F
Cure Time	12 hours initial cure
Packaging	Pint, Quart and Gallon Kits

Mixing and Application Instructions

Add entire contents of the Part B container into the Part A container. Using a mixing stick or slow speed drill, thoroughly mix until streak free while being careful to avoid whipping air into the mixture. Apply the **CAMMO FLEX** by hand, brush or trowel to surface in thin layers up to 1/4" thick. Allow a 6 hour initial cure before applying additional layers of **CAMMO FLEX** and allow 24 hour cure before coating or painting the **CAMMO FLEX**.



POLY GEM, Inc.
P.O. Box 609
West Chicago, IL 60186

www.polygem.com
Ph: (630) 231-5600
Fx: (630) 231-5604