

# E-Z SCULPT

## EPOXY SCULPTURING CLAY

- NO SOLVENTS
- NON-TOXIC
- SANDABLE
- PAINTABLE
- PIGMENTABLE

**\*ENVIRONMENTALLY SAFE**

**\*CLEANS UP WITH WATER**

**E-Z SCULPT** is a 100% solids epoxy system specially formulated to a workable 'clay like' consistency for sculpturing and modeling projects. **E-Z SCULPT** will cure into an extremely strong and durable plastic that is easily sanded or shaped. **E-Z SCULPT** can be tinted or painted and will even accept stains. **E-Z SCULPT** bonds well to most surfaces including fiberglass, foams, metal, wood and concrete. **E-Z SCULPT** is solvent free so it won't melt or dissolve foam surfaces.

**E-Z SCULPT** is used as a free form sculpturing medium or applied as a textured veneer over other surfaces. **E-Z SCULPT** is ideal for small or intricate detail work where strength and durability are desired. **E-Z SCULPT** can also be used as a patching compound to repair broken or damaged exhibits.

### PROPERTIES OF E-Z SCULPT

Compressive Strength ASTM D-695	14,500 psi (min)
Tensile Strength ASTM D-638	5,500 psi (min)
Viscosity	Clay Putty
Mix Ratio	1:1
Pot Life	60-90 minutes @70°F
Cure Time	8-12 hours
Packaging	Pint, Quart and Gallon Kits

### MIXING INSTRUCTIONS

Gather equal amounts of Part A and Part B by volume. Wearing protective gloves, begin to knead the two parts together until streak free and uniform in color. Small amounts of water may be used to help prevent the **E-Z SCULPT** from sticking to the gloves. Form or shape as desired.

**POLYGEM, Inc.**  
**P.O. Box 609**  
**West Chicago, IL 60186**

**www.polygem.com**  
**Ph: (630) 231-5600**  
**Fx: (630) 231-5604**